

Model:  
**LUMINO 10**

## Pipe Inspection System Push-rod Camera

- DN70 to DN150 pipes, 60 m cable
- Excellent lighting thanks to 30 LEDs



**C40BT**

### Accessories

1 x DVR remote control, 1 x charger/AC adaptor, 1 x connecting cable, 1 x centralizer, 1 x built-in Li-Ion battery, 1 x notice

### Order codes

Codes	Specifications
CST10S-C40BT-60MC (standard)	Reel with 60 m cable, meter counting, 512 Hz transmitter

### Parameters



**Camera Head  
C40BT**

Model: C40BT  
 Diameter range of service: DN70 - DN150  
 Dimensions:  $\Phi$  40 x 42 mm  
 Passage of elbows:  $\geq$  70 mm  
 512 Hz transmitter: built-in  
 Materials: housing in stainless steel, lens in sapphire crystal  
 Focal length: 10 to 20 cm, fixed  
 Resolution: 0.5 mega-pixel  
 Lighting: 30 LEDs  
 Waterproof: IP68, 1 bar Max.  
 Operational temperature: -20°C to 55°  
 Weight: 154 g



**Cable Reel  
CR33**

Cable material: fibre glass  
 Diameter & length:  $\Phi$  8 mm & 60 m  
 Meter counting: built-in  
 Power supply: by the control station  
 Protection rating: splash-proof  
 Operational temperature: -28°C to 50°C  
 Weight & dimensions: 14,9 kg, 52 x 28 x 61 cm  
 Screen: 10" TFT, 800 x 600 PX resolution



**Control Station  
CST10S**

Autonomy:  $\geq$  4 h  
 Power supply: 220 VAC / Li-Ion battery  
 Photo / video (JPEG / AVI) / audio Recording  
 Ports: 1 x USB, 1 x SD, 1 x video input, 1 x video output  
 Case: standard in ABS, splash-proof  
 Weight & dimensions: 2.5 kg, 27 x 22 x 10 cm