

Model:  
**KAMI**

## Pipe Inspection System Portable Push-rod Camera

- DN20 to DN50 pipes, 10 m / 20 m / 30 m / 40 m cable
- Compact design: highly adapted to narrow or difficultly accessible areas



**C12B**

### Accessories

1 × DVR remote control, 1 × charger/AC adaptor, 1 × connecting cable, 1 × centralizer, 1 × built-in Li-Ion battery, 1 × notice

### Order codes

Codes	Specifications
CST7M-C12B-CR12-20M	Portable reel, 20 m cable (standard)
CST7M-C12B-CR12-30MC	Portable reel, 30 m cable, meter counting (standard)
CST7M-C12B-CR12-10M	Portable reel, 10 m cable (in option)
CST7M-C12B-CR12-30M	Portable reel, 30 m cable (in option)
CST7M-C12B-CR12-40M	Portable reel, 40 m cable (in option)
CST7M-C12B-CR12-40MC	Portable reel, 40 m cable, meter counting (in option)

### Parameters



**Camera Head  
C12B**

Model: C12B  
 Diameter range of service: DN20 - DN50  
 Dimensions:  $\Phi$  12 × 22 mm  
 Passage of elbows:  $\geq$  35 mm  
 Materials: housing in stainless steel, lens in sapphire crystal  
 Focal length: 5 to 15 cm, fixed  
 Resolution: 0.4 mega-pixel  
 Lighting: 8 LEDs  
 Waterproof: IP68, 1 bar Max.  
 Operational temperature: -20°C to 55°  
 Weight: 45 g



**Cable Reel  
CR12**

Cable material: fibre glass  
 Diameter & length:  $\Phi$  4.8 mm & 10 m / 20 m / 30 m / 40 m  
 Meter counting: in option for 30 m and 40 m cables  
 Power supply: by the control station  
 Protection rating: splash-proof  
 Operational temperature: -28°C to 50°C  
 Dimensions: 32 × 32 × 11 cm



**Control Station  
CST7M**

Screen: 7" TFT, 800 × 480 PX resolution  
 Autonomy:  $\geq$  4 h  
 Power supply: 220 VAC / rechargeable Li-ion battery  
 Photo / video( JPEG / AVI) / audio recording  
 Ports: 1 × USB, 1 × SD, 1 × video input  
 Case: small, ABS, splash-proof  
 Weight & dimensions: 2,5 kg, 27 × 22 × 10 cm